

Cross reference data sheet | ERC 21X

ERC 21X controllers for Commercial Refrigeration

4

push buttons, a big display and an intuitive menu structure ensure superior ease of use.



Danfoss	Characteristics	Eliwell	Carel	Dixell	AKO	Full Gauge	Other Danfoss
ERC 211 1 relay	<ul style="list-style-type: none"> • 230 V (115 V) • 1 relay 16 A • 1 probe: <ul style="list-style-type: none"> - NTC 5 K - NTC 10 K - PTC - PT1000 • 1 Digital Input 	IC 901 EWPLUS 902 EWPLUS 961 ID 961 ID 961LX IDPlus 902 IDPlus 961	IR33(Smart) S PJEZS	XR 01CX XR 10CX XR 20CX XR 110C XR 120C	AKO D141XX	MT512	EKC102A
ERC 213 3 relay	<ul style="list-style-type: none"> • 230 V (115 V) • 3 relay 16 A, 8 A, 3 A • 2-3 probe: <ul style="list-style-type: none"> - NTC 5 K - NTC 10 K - PTC - PT1000 • 1-2 Digital Input • 1 Input is configurable as analog/digital 	EWPLUS 971 ID 961A ID 970 ID 970LX ID 971 ID 971LX IDPlus 971	IR33(Smart) Y PJEZY	XR 30CX XR 40CX XR 130C XR 140C	AKO D142XX		EKC 102B
ERC 214 4 relay	<ul style="list-style-type: none"> • 230 V (115 V) • 4 relay 16 A, 8 A, 3 A, 2 A • 2-3 probe <ul style="list-style-type: none"> - NTC 5 K - NTC 10 K - PTC - PT1000 • 1-2 Digital Input • 1 Input is configurable as analog/digital 	ID 975LX ID 985LX	IR33(Smart) C	XR 70CX			